

400 SQ FT / GAL YIELDS 2 MILS D.F.T.
 TIME TO OVERCOAT - 80° F – 8 HRS
 TIME TO LAUNCH – 16 HOURS
 2 COATS, 3RD ON WATERLINE

DEWAXER 973
 REDUCER 974
 – AS REQUIRED FOR PROPER
 FLOW AND PERFORMANCE

“Copper Pro SCX Hard™ was the ONLY product rated “EXCELLENT” in the high copper modified epoxy category, and beat Pettit® Trinidad™, Trinidad SR™, Trinidad Pro™ & Trinidad 75™, Interlux Ultra™, Ultrakote™, and Seahawk® Tropikote Biocide Plus™ & Tropikote™ hands down”, March 2009 - PRACTICAL SAILOR.

Alternative Product Replacements for: Interlux Ultra™, Pettit Trinidad SR™ and Pettit Trinidad Pro™



OLD LABEL:
 Copper Pro SCX 67 Hard


NEW




COPPER PRO™ SCX™ HARD 67
 Full Season
 Boosted Modified Epoxy
 67% Copper

Boosted with SCX - Slime Control Xtra.

COPPER PRO™ SCX™ HARD is the highest performance modified hard epoxy performance products on the market today. The highest copper content in our line, and in addition our performance booster SCX™ (Slime Control Xtra™) provides outstanding protection against slime, grass and weed. Continual release of biocide makes this modified hard epoxy most effective for anti-fouling protection. Superior protection against hard and soft growth in extreme fouling conditions. Perfect for powerboats and sailboats, and can be applied directly over properly prepared epoxies and vinyls, and most any other hard bottom paints.




8111
 ROYAL BLUE



8112
 MARINE BLACK



8113
 ADMIRAL GREEN



8114
 REGATTA RED

400 SQ FT / GAL YIELDS 2 MILS D.F.T.
TIME TO OVERCOAT - 80° F - 8 HRS
TIME TO LAUNCH - 16 HOURS
2 COATS, 3RD ON WATERLINE

DEWAXER 973

REDUCER 974
- AS REQUIRED FOR PROPER
FLOW AND PERFORMANCE

NEW!




Alternative Product
Replacements for: Interlux Micron
CSC™ and Pettit Horizons™


COPPER SHIELD SCX HARD™

Full Season Boosted Modified Epoxy 45% Copper

Copper Shield™ SCX Hard provides full season antifouling protection against barnacles, algae and hydroids in salt and fresh water on boat bottoms only. SCX booster protects against algae and grassed. Its modified epoxy base renders a smooth finish with durability and abrasion resistance. Copper Shield™ SCX Hard releases biocide by the exposure of paint film to the water. Copper Shield™ SCX Hard has universal application over all types of properly prepared bottom paints (except aluminum). For use on fast fiberglass boats, as well as wood and steel hulls.




8311
ROYAL BLUE



8312
MARINE BLACK



8313
ADMIRAL GREEN



8314
REGATTA RED

400 SQ FT / GAL YIELDS 2 MILS D.F.T.
TIME TO OVERCOAT - 80° F - 8 HRS
TIME TO LAUNCH - 16 HOURS
2 COATS, 3RD ON WATERLINE

DEWAXER 973

REDUCER 974

- AS REQUIRED FOR PROPER FLOW AND PERFORMANCE




Kolor™ was rated GOOD in the aluminum safe, bright color category, and beat Interlux® Pacifica™, Trilux 33™, Pettit® Alumacoat SR™, March 2009 - PRACTICAL SAILOR.


Alternative Product Replacements for: Interlux Trilux™, Interlux Trilux 33™ and Pettit Vivid™

KOLOR™ - Bright Colors, Aluminum, Trailerable Boats **Multi-Season Ablative** **45% Copper Thiocyanate** **Aluminum & Fiberglass**

KOLOR™ bottom paint has the cleanest, brightest colors and the most selection for bottom paint on the market today. Not only do we have the whitest white and the blackest black, we also have 100's of color combinations to choose from. Combine all of that with a multi-season self polishing ablative copolymer, and our bottom paint line is as effective as it is clean & vibrant. This product provides antifouling protection against barnacles, algae and hydroids in salt and fresh water on boat bottoms only. This product has universal application over all types of properly prepared bottom paints. For use on fiberglass, aluminum, wood & steel hulls.




8611
ROYAL BLUE




8612
MARINE BLACK



8613
ADMIRAL GREEN



8614
REGATTA RED



8616
WHITE

300 SQ FT / GAL YIELDS 2 MILS D.F.T.
 4-5 coats to build 10 mils D.F.T.
 Pot Life 5 Hours.

DEWAXER 973

REDUCER 974

– AS REQUIRED FOR PROPER
 FLOW AND PERFORMANCE

OVERCOAT INFO

	Between Coats		Last Coat / 1ST Coat Of Antifouling
	Min	Max	
50-60F	5 hrs	1 week	7 - 9 HOURS
60-80F	3 hrs	1 week	5 - 7 HOURS
80-90F	2 hrs	1 week	3 - 5 HOURS



BOTTOM PROTECT™ 8000A/8000B HIGH BUILD EPOXY PRIMER

- ▶ BOTTOM PROTECT™ 8000A / 8000B HIGH BUILD EPOXY PRIMER provides a seamless high build Epoxy Coating. This seamless high build epoxy creates an impermeable water barrier. BOTTOM PROTECT™ 8000A / 8000B HIGH BUILD EPOXY PRIMER eliminates any direct path for water migration.
- ▶ BOTTOM PROTECT™ 8000A / 8000B HIGH BUILD EPOXY PRIMER is a heavy duty 3:1 epoxy coating that prevents water absorption and blistering of your fiberglass hull.
- ▶ Our fast overcoating application allows the professional or do-it-yourself applicator to achieve 10 mils of protection in a single weekend.
- ▶ No harmful methylene chloride, and has superior sag control resistance.
- ▶ Also an excellent primer for all underwater metal hulls, keels, aluminum, steel, lead, cast iron, stainless and bronze.
- ▶ For specific Epoxy Barrier Coat Information, read the product label thoroughly, or refer to Tech Bulletin # 8006 on the web or call for a copy.



BOTTOM PROTECT™ 8001A/8001B HIGH BUILD EPOXY SEALER

- ▶ **BOTTOM PROTECT™ 8001A / 8001B HIGH BUILD EPOXY SEALER** is a clear high build epoxy sealer for use when gel coat and fiberglass laminate requires sealing. This product is 100% solids, no solvents can be trapped behind the epoxy.
- ▶ This product is used in conjunction with **BOTTOM PROTECT™ 8000A / 8000B HIGH BUILD EPOXY PRIMER**.
- ▶ Overcoat at 3-4 hours with **8000A / 8000B BOTTOM PROTECT HIGH BUILD EPOXY PRIMER**
- ▶ For specific Epoxy Barrier Coat System Information, read the product label thoroughly, or refer to Tech Bulletin #8006 either on the web or call for a copy